

Turn your dream into reality



TU1000



TU2200T



TLU2450/1

The new American line

7'
6'
5'
4'



TU1000

\$4,990



TU1000T

\$6,290



TU1450
TU1450T

\$7,190



TU2200
TU2200T

\$7,990



TU2200T/51

\$8,990



TU2700/4

\$10,990



TTU2700

\$12,990



TTU2700/5
TTU2700/75

\$13,490
\$14,990



TLU2000/91

\$11,990



TLU2450/1

\$14,990





Product Code	Small Models	Suggested Retail Price	Weight	Height	Footprint		Bakeoven		Firebox		Wood Length	Load per Firing	Heat Release Duration		
					Width	Depth	W	D	W	D			@ 100%	@ 50%	@ 25%
		USD	lb	in.	in.	in.	in.	in.	in.	in.	in.	lb			
<i>TU1000</i>	TU1000 4' height, base vent	\$4 990	2 085	48,4	33,1	18,9			12,2	9,6	10	17	2 hrs	10.5 hrs	18 hrs
<i>TU1000T</i>	TU1000 5' height, top vent	\$6 290	2 675	60,2	33,1	18,9			12,2	9,6	10	21	2 hrs	13 hrs	23 hrs
<i>TU1450</i>	TU1450 5' 3" height, base vent	\$7 190	2 950	62,6	35,4	18,9			12,2	9,6	10	24	3.5 hrs	12.5 hrs	22 hrs
<i>TU1450T</i>	TU1450 5' 3" height, top vent	\$7 190	3 050	62,6	35,4	18,9			12,2	9,6	10	24	2 hrs	13 hrs	23 hrs
	Mid-Sized Models														
<i>TU2200</i>	TU2200 5' height, base vent	\$7 990	4 050	60,2	40,2	23,6			15,7	14,4	14	32	4.5 hrs	17.5 hrs	26 hrs
<i>TU2200T</i>	TU2200 5' height, top vent	\$7 990	3 950	60,2	40,2	23,6			15,7	14,4	14	32	4.5 hrs	14.5 hrs	25 hrs
<i>TU2200T/51</i>	TU2200 6' height, top vent	\$8 990	4 600	72,0	40,2	23,6			15,7	14,4	14	37	n/a	n/a	n/a
<i>TLU2000/91</i>	TLU2000 5' 5" height, bakeoven, base vent	\$11 990	4 630	65,0	36,6	29,5	15,4	18,3	14,4	12,0	12	37	5.5 hrs	20.5 hrs	31.5 hrs
	Large Models														
<i>TTU2700/4</i>	TTU2700 6' height, top vent	\$10 990	5 685	72,0	40,2	29,5			15,7	14,4	14	45	5 hrs	21.5 hrs	32.5 hrs
<i>TTU2700</i>	TTU2700 7' height, double door firebox, top vent	\$12 990	6 550	83,9	40,2	29,5			15,7	24,8	20	52	5 hrs	18.5 hrs	30 hrs
<i>TTU2700/75</i>	TTU2700 7' height, bakeoven, top vent	\$13 490	6 350	83,9	40,2	29,5	16,5	17,1	15,7	14,4	14	51	5 hrs	18.5 hrs	30 hrs
<i>TTU2700/5</i>	TTU2700 7' height, double door firebox & bakeoven, top vent	\$14 990	6 700	83,9	40,2	29,5	16,5	17,1	15,7	24,8	20	54	5 hrs	18.5 hrs	30 hrs
<i>TLU2450/1</i>	TLU2450 5' 6" height, bakeoven, base vent	\$14 990	6 260	66,1	42,5	35,4	17,7	21,9	15,7	14,4	14	50	6 hrs	23.5 hrs	36 hrs
	Accessories														
<i>2700/6</i>	Soapstone four-sided bench for TTU2700	\$3 690	1 780	16,5	63,8	53,1									
<i>see dealer</i>	Soapstone two-sided bench for TU2200 (+ 2 3/8" heater)	\$1 265	550	14,2	68,5	27,8									
<i>JO70US</i>	Soapstone chimney element, square	\$290	150	11,8	15,4	15,4									
<i>ML10L</i>	Soapstone tiles, per box of 9 "Tulikivi Classic" tiles	\$199	55	0,4	11,8	11,8									
<i>1270/1272/1</i>	Stainless steel chimney damper 6" / 7" / 8" dia.	\$335/350/360	7/7/8												
<i>5123/5150</i>	Electric elements 2 kW / 3 kW	\$1090/1290	6/12												

Additional Information

Tulikivi Soapstone Heaters are assembled on site by a Tulikivi installer, are UL/ULC safety tested & listed, carry a 5-year warranty and are exempt from compliance to EPA NSPS 2015. Suggested Retail Prices do not include delivery, on-site assembling, structural support, chimney and optional components such as heat shields, hearth tiles, benches & other accessories. All measurements converted from millimeters. Numbers for Weight and Heat release duration are rounded.

Performance data according to "EN – Declaration of Performance". All models tested to EU Standard EN15250. *TU1000T* & *TU1450T* tested together. *TTU2700*, *TTU2700/5* & *TTU2700/75* tested together.

"Max load per firing" is based on 8 pounds of firewood per 1000 pounds of heater weight. Firings must be at least 10 hours apart.

"X hrs @ Y %" means at least Y % of maximum heat output will be delivered for X hours (after maximum heat output is reached).

Recommended flue diameters : 6" or 7" for small models, 7" or 8" for medium sized and large models. Min. chimney height (measured from the floor) : 20' for models with bakeovens, 15' otherwise.

Clearances to combustibles : 20" to back, 14" to sides, 10" to top and 48" to front. Can be reduced to 3" with a Tulikivi specified heat shield. Clearance for soapstone chimney elements : 1"

Floor protection : 3/8 minimum thickness of non-combustible material, extending 8" from the sides, 8" from the back (unless there is a heat shield) and by 16" from the front of the heater.